




UDAY[®]
GRANITO

BOOKMATCH
COLLECTION

www.udaygranito.com

CREATING CAPTIVATING environments



FEATURES



9MM
Thickness



Frost
Resistance



High Load
Resistance



Thermal
Impact



Anti-slip
Finish



Removable &
Reuse



Easy to
Install



Chemical
Resistance



Ecological
Finish



Fire
Proof



THE POWER
TO TRANSFORM
SPACES



**LARGEST
PRODUCTION CAPACITY**

**600x
1200mm**

GVT / PGVT

The **UDAY GRANITO** large-sized slabs are ideal for surfaces that demand maximum **HYGIENE, STRENGTH AND AESTHETIC HARMONY.**

www.udaygranito.com




DIMENSION
600x1200 mm
2'x4' | 24"x48"

FINISH
POLISHED GLOSSY
SURFACE


UDAY[®]
GRANITO

FLARE ONYX




BROWN GREY

FOPLA



BEIGE

IMPER



CHOCO IVORY WHITE

JESTIC




BROWN GREY

KAMA




NATURAL

KUMIL



BLUE WHITE

MASSON



AZUL BEIGE GREY

MORISIS




AZUL BROWN GREY

ONTIVIA ONYX




GREY

OTIS



GREY

POTA



BLUE GREY

SAGON



WHITE

VECTO




GREY

ZABRO



NATURAL

ZETER



GREY

**FLARE ONYX
GREY**

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS



**FLARE ONYX
BROWN**

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS





FOPLA BEIGE


DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE


APPLICATIONS



IMPER WHITE

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES




BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE


APPLICATIONS



IMPER IVORY

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE


APPLICATIONS



IMPER CHOCO

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS





JESTIC BROWN

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS



JESTIC GREY

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS





KAMA NATURAL


DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS





KUMIL BLUE

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES




BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS



KUMIL WHITE

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS






MASSON AZUL

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS



MASSON GRAY

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES




BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE


APPLICATIONS



MASSON BEIGE

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS





MORISIS BROWN

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS



MORISIS GREY

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE


APPLICATIONS



MORISIS AZUL

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS






**ONTIVIA ONYX
GREY**

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE


APPLICATIONS



OTIS GREY



DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



FINISH
POLISHED GLOSSY
SURFACE


APPLICATIONS



POTA GREY

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES




BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE


APPLICATIONS



POTA BLUE

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES




BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS






SAGON WHITE

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES





BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE


APPLICATIONS



VECTO GREY

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES




BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS






ZABRO NATURAL

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES



BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE


APPLICATIONS



ZETER GREY

DIMENSION
600x1200 mm
2'x4'
24"x48"

RANDOM
FACES





BACK TO INDEX



FINISH
POLISHED GLOSSY
SURFACE

APPLICATIONS







FLEXURAL RESISTANCE

It has the ability to resist deformation under load. It deforms significantly but does not break



FROST PROOF

they are porous and absorb water easily. These tiles have relatively high frost resistance.



EAR RESISTANCE

It is the core feature it helps to give the perfect finish to edges while cutting.



SCRATCH RESISTANCE

It is highly recommended for its scratch resistance property.



THERMIC IMPACT RESISTANCE

This provides the surface to tolerate the impact of objects falling on them.



SLIP RESISTANCE

Our tiles have an abrasive grit on their surface, increasing their slip resistance significantly.



STAIN RESISTANCE

It is durable and easier to clean and retain the original exquisiteness every time.



CHEMICAL RESISTANCE

Its highly resistant to harsh chemical agents like alkalis, acids, household chemicals, and swimming pool salts.



ABSORPTION RESISTANCE

Our tiles are coated with liquid glass and hence absorb less water.



EASY TO CLEAN

It's highly convenient as it is easy to clean and it provides comfort with ease.



EASY TO INSTALL

This creation is super easy to apply it can be applied without any tool or laying instructions.



ECO LOGICAL

We are committed to the environment and recognize that sustainability is a significant and crucial part of our journey.



technical specification

We are delighted to introduce our latest line of high-quality tiles, designed to meet the exacting standards of our esteemed clientele. we pride ourselves on delivering superior products that combine functionality, durability and aesthetic appeal.

600X1200MM

Tiles In Every Space

We understand that choosing the right tiles for specific application areas is crucial for achieving both functionality and aesthetic appeal. That's why we're delighted to introduce you to our comprehensive selection of tiles designed to excel in various environments:



Dining Hall



Bedroom



Bathroom



Living Room



SPA



Restaurant



Airport



Railway Station



Outdoor



Swimming Pool Area



Garden Area




Parking Area


600X1200MM




LAYING INSTRUCTION




DRY Laying
**On
Grass**



Laying on
Garvel



Laying on
**Screed
With Adhesive**



Laying on
**Raised
Floor**



TECHNICAL SPECIFICATION

CHARACTERISTIC	STANDARD AS PER ISO 13006:2018/ EN14411 Gr.Bla	MEAN VALUE OF UDAY	TEST METHOD
Regulatory Properties			
Deviation in length and width	± 0.30 % (±1.00mm)	± 0.10 %	ISO 10545-2
Deviation in thickness	± 5.00 % (±0.50mm)	± 4.00 %	ISO 10545-2
Straightness in side	± 0.30 % (±0.80mm)	± 0.10 %	ISO 10545-2
Rectangularity	± 0.30 % (±1.50mm)	± 0.10 %	ISO 10545-2
Surface flatness central curvature	± 0.40 % (±1.80mm)	± 0.20 %	ISO 10545-2
Surface flatness edge curvature	± 0.40 % (±1.80mm)	± 0.20 %	ISO 10545-2
Surface flatness warpage	± 0.40 % (±1.80mm)	± 0.10 %	ISO 10545-2
Surface quality	> 95% defects free	> 95% defects free	ISO 10545-2
Small Color Difference(For Plain Color)	ΔE <1.00	ΔE < 0.30	ISO 10545-16
Glossiness (Polished)	as per mfg.	Gloss Value > 90	Glossmeter 60°
Glossiness (Matt)	as per mfg.	3° < GLOSS < 7°	Glossmeter 60°
Glossiness (satin/Posh)	as per mfg.	7° < GLOSS < 18°	Glossmeter 60°
Structural Properties			
Water absorption	0.50 % ≤ Ev ≤ 3.00 %	0.060 % ≤ Ev ≤ 3.00 %	ISO 10545-3
Bulk density	as per mfg.	> 2.28 gm/cc	ISO 10545-3
Massive Mechanical Properties			
Modulus of rupture	Min. 30.0 N/mm ²	Min. 35.0 N/mm ²	ISO 10545-4
Breaking strength thickness ≥7.5	Min. 700.0 N	Min. 1000.0 N	ISO 10545-4
Breaking strength thickness ≥7.5	Min. 1100.0 N	Min. 1300.0 N	ISO 10545-4
Breaking strength thickness ≥7.5(For ≥15mm)	Min. 1100.0 N	Min. 1800.0 N	ISO 10545-4
Surface Mechanical Properties			
MOH'S hardness	as per mfg.	Polished Min 4* / Satin,Posh & Matt Min 6	BS EN 15771
Surface abrasion resistance	as per mfg.	Polish Min. Class 2, Satin & Posh Min. Class 3, & Matt Min. Class 4	ISO 10545-7
Deep abrasion resistance	Max. 175mm ³	Max. 132mm ³	ISO 10545-6
Thermal Hydrometric Properties			
Moisture expansion	Max. 0.06%(0.6mm/m)	0.02mm/m	ISO 10545-10
Thermal expansion(COE) at 100°C	as per mfg.	Max. 6.0 x 10 ⁻⁶	ISO 10545-8
Thermal shock resistance	Min. 10 Cycle	Min. 10 Cycle	ISO 10545-9
Impact resistance(COR)	Min. 0.55	Min. 0.55	ISO 10545-5
Frost resistance	as per mfg.	Frost Proof	ISO 10545-12
Chemical Properties			
Resistance to staining glazed	Min. Class 3	Min. Class 4	ISO 10545-14
Resistance to household chemicals & swimming pool salts glazed	Min. Class GB	Min. Class GA	ISO 10545-13
Resistance to low concentrate acid and alkalis glazed	as per mfg.	Min. Class GLA**	ISO 10545-13
Resistance to high concentrate acid and alkalis unglazed	as per mfg.	Min. Class GHB**	ISO 10545-13
Safety Properties			
Skid resistance (COF-WET PENDULAM)##	as per mfg.	Glossy P0(<12),Satin, Posh ≥P1(12-24) Matt ≥P2(25-34)	BS 7976-2
Slip resistance - (Satin / Matt (DCOF) (R value)##	as per mfg.	R9 to R13**	DIN 51130
Fire resistance	as per mfg.	Fire Proof	N.A.

UDAY[®]
GRANITO

PACKING DETAILS

PRODUCT	SIZE	THICKNESS	TILES / BOX	COVERAGE AREA / BOX	WEIGHT
GVT-PGVT	600x 1200mm	8.5mm	2 pcs.	1.44 sq. mtr.	27.300 KG (APPROX)

UDAY GRANITO LLP

Sr. No. 81 & 86 p2, 8-A National Highway,
Sartanpar Road, At: Ratavirda - 363621 Tal: Wakaner,
Dist: Morbi, Gujarat, India.

www.udaygranito.com

info@udaygranito.com

+91 99099 72245

+91 98253 23287